

ACT1100 / ACT1700 Standard Clock Oscillators

The ACT1100 is a full size through hole oscillator. The ACT1700 is a half size through hole oscillator. The popularity of these families still remains even after the advent of smaller surface mount devices. With wide frequency and operating temperature ranges, these series offer low cost & good reliability for ATM, Networking, Microprocessor and Consumer applications. An option with a supply voltage of 2.5V is available please contact our sales desk for details. A 10ppm stability double package option is available, please enquire. For wider frequency range < 500KHz, >150MHz (120MHz) please refer to the ACT1100HS/1700HS data.



Specification


Parameter	Symbol	Specification			Condition
		TTL	HCMOS	TTL/HCMOS*	
Frequency Range (MHz)	fo	1.0~ 155.0	0.5~150 (120***)	1.0~150(120***)	Please Specify
Supply Voltage	VDD	5.0VDC ±10%	3.3 ,5.0VDC±10%	5.0VDC ±10%	Please Specify
Frequency Stability	Δf/fo	±10ppm**, ±25ppm, ±50ppm and ±100ppm			Please Specify
Temp Operating Range	Topr	0 ~ +70°, -10 ~ +70°C **			Please Specify
Temp Storage Range	Tstg	-40~85°C			
Supply Current	Iop	15mA max(3.3VDC) 25mA max(3.3VDC)	25mA max(5.0VDC) 35mA max(5.0VDC)		0.5 - 27MHz 27 - 125MHz
Duty Cycle	TW/t	40/60%, 45/55% TTL 40/60%, 45/55% HCMOS			Measured at +1.4Volts Measured at 50% VDD
Output Level '0'	VOL	TTL 0.4V max, HCMOS .33V max TTL 0.4V max, HCMOS 0.5V max			VDD = 3.3V VDD = 5.0V
Output Level '1'	VOH	TTL 2.4V min, HCMOS 2.97V min VDD TTL 2.4V min, HCMOS 4.5V min VDD			VDD = 3.3V VDD = 5.0V
Output Logic		[TTL], [(HCMOS), [HCMOS/TTL (Universal)]			Please Specify
Output Load		TTL 10 Gates HCMOS 15 pF			
Rise & Fall Time	tr/ft	TTL 10nSec max, 3nSec typical Measured between 0.4V ~ 2.4V (RL = 390Ω ; CL = 15pF) CMOS 10nSec max, 3nSec typical Measured between 10%~ 90% VDD (CL = 15pF)			
Start-up Time		4mSec max,			
Option on Pin 1****		Tri State or No Connection****			Please Specify
Aging		±5ppm / year max			@25°C

* Universal Output ** Double package tight stability option *** ACT1700 **** ACT1700 <100MHz for Tri state option

Available Stabilities (Note **)

	±10ppm**	±25ppm	±50ppm	±100ppm
0 ~ 70 °C	✓	✓	✓	✓
-10 ~+70°C	Enquire	✓	✓	✓
-40 ~ +85°C		Enquire	Enquire	Enquire

Dimensions (mm)



**Plating Material on leads
SnAgCu**

**Soldering conditions
please refer to page 3**

ACT1100 ('V' SERIES)
ACT1700 ('CL' SERIES)

Please note that all parameters can not necessarily be specified in the same device

Customer to specify : Frequency, Operating Temperature Range, Frequency Stability, Supply Voltage, Output, Duty Cycle, Output Enable (Tristate) If required
 In line with our ongoing policy of product evolution and improvement, the above specification may be subject to change without notice

ISO9001:2000 Registered

For quotations or further information please contact us at:



3 The Business Centre, Molly Millars Lane, Wokingham, Berkshire, RG41 2EY, UK

<http://www.actcrystals.com>

ACT1100 / ACT1700 Standard Clock Oscillators

Reliability tests

Test	Test Method	Measurement Requirements
Leak	Helium bomb: Pressure 200kpa Time 70 min pressure release 5 min measure within 30min	$\leq 4 \times 10^{-9} \text{pa.m}^3/\text{s}$
Drop	750mm height. 3 drops. Onto wood.	Specification as per page 1 must be met.
Shock	Peak acceleration 981m/s ² Pulse duration 6ms Each of X, Y and Z axis. 3 shocks each axis	
Vibration	10 to 55Hz and return to 10Hz amplitude 1.5mm sweep time 1min. 2 hrs each of X, Y and Z axis. Total test time 6 hrs	
Resistance to Soldering Heat	As per profile fig.1 below and/or soldering iron applied for 5s max tip temperature 350±10°C	
Aging	85±3°C 30 days measurements after at least 1 hr at atmospheric conditions.	
High Temperature Storage	105±3°C 16 hrs measurements after at least 1 hr at atmospheric conditions	
Low Temperature Storage	-55±3°C 2hrs measurements after at least 1 hr at atmospheric conditions	
Thermal Cycling	100cycles to the temperature profile fig 2 below. Measurements after at least 1 hr at atmospheric conditions	
Damp Heat Constant	Temperature 40±2°C RH 90–95% for 56 days. Measurements after at 1 hr at atmospheric conditions	
Solderability	255±5°C for 10±0.5s using Rosin resin methyl alcohol flux Solvent (1:4) dipped to a nominal depth of 0.5mm.	



In line with our ongoing policy of product evolution and improvement, the above specification may be subject to change without notice

ISO9001 Registered


For quotations or further information please contact us at:

3 The Business Centre, Molly Millars Lane, Wokingham, Berkshire, RG41 2EY, UK

<http://www.actcrystals.com>


ACT1100 / ACT1700 Standard Clock Oscillators

Fig. 3 Recommended Wave Soldering Profile




Application circuits

CMOS Test Circuit



Output to oscilloscope and/or frequency counter

TTL Test Circuit



Output to oscilloscope and/or frequency counter

In line with our ongoing policy of product evolution and improvement, the above specification may be subject to change without notice


ISO9001Registered

For quotations or further information please contact us at:
3 The Business Centre, Molly Millars Lane, Wokingham, Berkshire, RG41 2EY, UK
<http://www.actcrystals.com>

ACT THROUGH HOLE CLOCK OSCILLATORS - PART NUMBERING

Highlight = Standard Specification / Parameter

Example :



Available Stabilities (Note 1)

	± 10 ppm**	± 25 ppm	± 50 ppm	± 100 ppm
0 ~ 70 $^{\circ}$ C	✓	✓	✓	✓
-10 ~ +70 $^{\circ}$ C	Enquire	✓	✓	✓
-40 ~ +85 $^{\circ}$ C		Enquire	Enquire	Enquire

NOTES :

- Note 1: Inclusive of 25 $^{\circ}$ C tolerance, operating temperature range, $\pm 10\%$ VDD change, Load change, aging, shock and vibration.
- Tighter Stabilities, Duty Cycles, Supply Voltages, Output Loads and other Operating Temperature Ranges may be available. As each of these specification parameters may impact on each other, it is not always possible to combine all options in one device. Therefore, if a specification not catered for above is required, please contact us directly for assistance.
- ACT are always happy to consider truly custom specification parts which may require non-standard specification parameters, specific testing, customer requested AQL requirements, non standard packaging or taping and reeling and custom marking. (MOQ DEPENDENT) Such devices would normally be allocated a custom specification (An ACT1100 device may have a part number such as HS2500L- C2222-PF)

ISO9001 Registered

For quotations or further information please contact us at:

3 The Business Centre, Molly Millars Lane, Wokingham, Berkshire, RG41 2EY, United Kingdom

<http://www.actcrystals.com>