11/F, GUANGDONG FINANCE BUILDING, 88 CONNAUGHT ROAD WEST, HONG KONG

Tel.: (852) 2548 2098 Fax: (852) 2858 2514,2858 2520,2549 3161 E-mail: db_buzzer@db.com.hk

www.db.com.hk ISO 9001

SPECIFICATIONS SHEET

PRODUCT TYPE : MAGNETIC TRANSDUCER

PRODUCT SERIES: <u>DBX</u>

DESCRIPTION: <u>MT TRANSDUCER 5V PIN NORYL</u>

ROHS COMPLIANT


COLOR: BLACK

ELECTRICAL SPECIFICATIONS

MODEL NO.		DBX05LFPN	
OPERATING VOLTAGE RANGE	(V)	3.0 ~ 8.0	
RATED VOLTAGE	(V)	5.0	
+ MAX. RATED CURRENT	(mA)	40.0	
COIL RESISTANCE	(Ω)	47.0 ± 5.0	
* COIL IMPEDANCE	(Ω)	80	
+ MIN. SOUND OUTPUT AT 10 cm	(dBA)	85	
RESONANT FREQUENCY	(Hz)	2400 - 40 ~ + 85	
OPERATING TEMPERATURE	(°C)		
TERMINAL		PIN	
HOUSING MATERIAL		NORYL	
WEIGHT	(g)	2.0	

⁺ Value applying rated voltage reasonant frequency, 1/2 duty, square wave

<u>DIMENSIONS</u> UNIT: mm



BOTTOM VIEW

Approved By:
Date: 13-Jun-2006

Prepared By Date: 13-Jun-2006

Modify:	Date:	By:

^{*} Value applying reasonant frequency, 1/2 duty, square wave, measuring current 60uA