



QUARTZ CRYSTALS

MHz range

SMD-version

model	KX - 9B		
frequency range	8,0 ~ 50,0 MHz		
mode	fundamental		
operating temperature	standard	-20° ~ + 70° C	
	available	-40° ~ + 85° C (=KX-9BT)	
	available	-40° ~ +105° C (=KX-9BE)	
frequency tolerance at +25° C	standard ± 50 ppm available ± 10 ~ ± 50 ppm		
temperature tolerance -20° ~ + 70° C -40° ~ + 85° C -40° ~ +105° C	standard ± 50 ppm, available ±10 ~ ± 50 ppm standard ±100 ppm, available ±20 ~ ± 100 ppm standard ±120 ppm, available ±30 ~ ± 120 ppm		
load capacitance C _L	standard 16 pF available 10 ~ 20 pF		
series resonance R ₁ max.	fundamental	8,0 ~ 16,0 MHz 16,1 ~ 20,0 MHz 20,1 ~ 50,0 MHz	100 Ohm 60 Ohm 40 Ohm
aging (first year)	± 2 ppm		
shunt capacitance C ₀ max.	5,0 pF		
drive level in mW max.	0,1		
contents of reel	1000 pcs.		
RoHS	since production start		
part no.	12.89400 ~ 12.89499		

